

ज्ञापांक.....3533...../आपूर्ति
95-1-14-2015

पुलिस महानिदेशक का कार्यालय, बिहार, पटना।

पटना,दिनांक- 21-8-15

सेवा में,

निदेशक,

सूचना एवं जनसम्पर्क विभाग,
बिहार, पटना।

विषय— निविदा आमंत्रण सूचना सं०-23/2015-16 के प्रकाशन के संबंध में।

निदेशानुसार उपर्युक्त विषय के संबंध में निविदा आमंत्रण सूचना सं०-23/2015-16 की पॉच प्रतियाँ (सी०डी० सहित) संलग्न करते हुए अनुरोध है कि इसे राज्य एवं राज्य से बाहर के प्रमुख समाचार पत्रों में (अंग्रेजी एवं हिन्दी) के अगले दो संस्करणों में प्रकाशित कराने की कृपा की जाय साथ ही पी०आर०डी० वेबसाइट पर भी प्रसारित करने की कृपा की जाय।

इस निविदा आमंत्रण सूचना का प्रकाशन किन-किन समाचार पत्रों में किया गया इसकी सूचना देने की कृपा की जाय।

अनु०-यथोपरि।


पुलिस महानिरीक्षक के सहायक (क्यू०),
बिहार, पटना।

प्रतिलिपि:— आई०टी० मैनेजर, पुलिस महानिदेशक का कार्यालय, बिहार, पटना को कृपया सूचनार्थ। कृपया इसे आज ही वेबसाइट पर अपलोड किया जाय।

- 17
6. In case of BP/BR items, test report of TBRL is compulsory.
 7. Firms participating in this tender shall also submit duly sworn affidavit to the effect that " this firm has not been black listed/debarred by any Government or Semi Government or Private Agency and no sister concern of this firm is participating in this tender."
 8. Firms participating in this tender shall also submit the self attested list of users of its equipments.
 9. All items shall be received at Central Clothing Store, Patna, therefore price should be quoted FOR Central Clothing Store, Phulwari Sharif, Patna.
 10. Firms will have to deposit a sum of Rs.50,000/- (Fifty Thousand) only as an earnest money in the form of Bank Draft duly pledged in favour of the undersigned along with the quotations.
 11. Technical Bids will be opened on schedule date and time in the office chamber of Police Headquarter. Representatives of the firms competing in the tender may remain present at the time of opening of the technical bid.
 12. The technical bids will be opened first and placed before the Technical Committee of the Police Headquarters, Bihar. If the technical bids are found satisfactory as per tender conditions, it will be put before Central Purchase Committee of the Police Headquarters, Bihar. The firms may be required to participate in the demonstrations of the quoted product and discussions with this committee.
 13. Any paper/document will not be accepted after opening the tender.
 14. Successful firm will have to enter into an agreement after depositing a sum of 5% of the total value of the order as security money in the form of Bank Guarantee duly pledged in favor of undersigned.
 15. The firm will be required to provide satisfactory service after the delivery of the product.
 16. The firm will be required to supply all the items within the stipulated time frame as mentioned in the purchase order.
 17. Payment for the delivered items will be made only after the acceptance report of the Inspection Committee of the Police Headquarters, Bihar.
 18. The firm whose quotation is approved by the Central Purchase Committee of the Police Headquarters, Bihar, shall be invited to enter into an agreement with the undersigned.
 19. It is compulsory to submit the duly filled chart attached herewith, along with the technical bid.
 20. Indexing of the requisite documents must be done and submitted along with the technical bid.
 21. Hands on training of the equipment must be imparted to the user group by the firm.
 22. Director General of Police Bihar, Patna reserves the right to reject any or all the quotations partially or fully without assigning any reason thereof.
 23. The Quantity indicated may increase or decrease at the time of issuing purchase order.


AIG (Q)
Bihar, Police

114

ELECTRONIC STETHOSCOPE

- Sensor : Air-coupled HIR sound transducer activated by diaphragm
- Amplifier : Solid-state integrated circuit gives 1 to 10 fold amplification in Model HG 900
- Volume : Continuously adjustable by graduated 1 to 5 potentiometer control
- Filter : 2 - Way Electronic Filter Switch
 - a) LO-Filter for low pitch sound;
 - b) HI-Filter for high pitch sound
- Mechanical : Glass epoxy sealed PCB, Unbreakable ABS/Cr-Metal body; Soft Polymer tubing / Ear-tips, Stainless Steel Binaural Spring.
- Power : One 3 Volt Lithium Cell : Type CR 2032, or equivalent.
- Size/Weight : Chestpiece: 5 cm round / 3 cm high; Y-tubing: 55 cms long. Black/Grey color - 180 gms - Carry Case: 27 x 15 x 5 cms

20/11/2015
05.8.15

13

TECHNICAL SPECIFICATIONS -TELESCOPIC MANIPULATOR

1. The equipment should be less than 15 Kgs. Should be usable with the help of a shoulder strap by a single bomb technician.
2. The equipment should offer a minimum safety distance of 4 meters.
3. The claws should be adjustable with opening distance of at least 15 cms (6 inches).
4. The Manipulator should be able to pick up a maximum weight of 10 Kg. when fully extended.
5. The battery pack power source should last for minimum 30 minutes of operations. The battery should be rechargeable.
6. The telescopic manipulator should have a break away tip arrangement, so that in case of possible explosion only the tip is damaged.
7. The equipment should be provided with various optional claws, which can be fitted and used as required depending on the shape of the object to be manipulated.

2006/14/01/60
05.8.15

Remote Operated Wire Cutter

Specifications

- Its able to cut electric wire upto dia 5 mm thickness remotely. (Option available till 10,15,20 & 25 mm)
- Works on inbuilt SMF rechargeable battery with universal charger (70-240 V, 50-60 hz
- Comes with a wired / cordless remote of minimum distance of 25 meters, option available upto 100 metres
- It's light weight , portable devise.
- Its possible to adjust the height of the equipment from 3 inches to 11 inches. Option also avilable till 2.2 metres.
- Self balancing tripod stand to stand on any time of hard/ soft ground.
- It has 360 degrees horizontal movement , with locking arrangement.
- It has option to adjust the y axis / angle of the cutter upto 45 deg.
- Its operatable on both AC and DC
- Modular design, easy to carry , remotely operatable.
- Can also be mounted on any ROV

2014/08/15
05.8.15

Telescopic prodder (non metallic)

Specifications:-

1. Robust & light weight.
2. Non magnetic material.
3. Non metallic tip.
4. Heavy duty plastic handle.
5. Telescopic rod with removable tip.
6. Extended length- 1 meter.
7. Closed length - $\frac{1}{2}$ meter.
8. Soft rubber grip.
9. Nylon carry case/webbing carrier.
10. Air craft aluminium LED torch.
11. Powder coated/ nickel coated.
12. As per DRDO/RDSO specification.

05.8.15
S. S. S.

110

Extention search mirror:-

Specifications:-

1. Mirror size : 7"x5"
2. Arm length : around 5ft (extendable)
3. Lighting : 2 cell torch
4. Sp. Features : fast viewing.
5. Application : inspection of small vehicles & inaccessible places.

2014/08/15
05.8.15

Under Vehicle Search Mirror

Specifications:-

1. Mirror :- 330x265mm (13x10.4") convex, glass mirror.
2. Illumination :- 2x6 watt fluorescent lamps in a splash proof acrylic housing with handle grip and 2m (6.6) flying lead, clip fastened to trolley base. Length : 15cm (6")
3. Handle :- 950mm (3ft) hinged aluminium handle.
4. Controls :- 3- way switch with off, latching and momentary positions.
5. Batteries :- powered by 10 D- Cell batteries with 8 hrs. back up time.

20/10/15
05.8.15

High Power Handheld Mobile Jammer

Technical Specifications

Output power: 2.5 watt
Maximum effective range: 20 meters
Antenna: External, Omni directional
Power supply: AC 110-240V, DC 12V
Working temperature: -15Å,°C to +60Å,°C
Working humidity: 5%-80%

Jamming System

Analog: NMT, TACS, AMPS
Digital: 3G, GSM, CDMA, DCS
2.4G: Bluetooth, Wifi

Jamming Frequencies

925-960 MHz: GSM 900
1805-1880 MHz: DCS, GSM 1800
2110-2170 MHz: 3G, CDMA, WCDMA
2400-2500 MHz: Wifi, Bluetooth

Physical Specifications

Product size: 113x65x30 mm
Product weight: 250 g
Package size: 208x153x85 mm
Package weight: 750 g
Battery Type: Lithium-Ion
Capacity: 1800 mAh
Charging time: 3 hours
Working time: 1.5 hours

2014/08/15
05.8.15

✓

Telescopic Prodder (Metallic)

Specifications:-

- It should be made with rust proof heavy steel.
- Two Fold threaded rods should be provided, front rod should go inside main rod when not in use/during transportations.
- Total length should be 80cm to 90 cm.
- One end should be sharp pointed and other end should be shock proof rubber grip.
- Total Weight should not be exceed more than 1 kg.
- It should be strong enough to dig all kinds of soils.

20/11/2016
05.8.15